Apple Writer][Reference Card

Commands using the CTRL key are shown as $[\]$. All commands may be entered in upper or lower case.

EDITING

BETTING	
Command	Effect
ESC ESC	Cursor move mode:
I	up one line
J	left one character
K	right one character
M	down one line
E	up 12 lines
S	left 24 characters or one word
D	right 24 characters or one word
X	down 12 lines
<	Deletes character(s)
>	Retrieves character(s) deleted
	by <
[B]	Moves cursor to file beginning;
1-2	sets Data Line arrow to >
[C]	Automatic case change; cursor
1-3	displays L or U
[D]	Changes direction of Data Line arrow
[E]	Moves cursor to file end; sets data
1-3	line arrow to <
[F]/{text}/{replacement}/	Finds and deletes {text} and
2-77	inserts {replacement}
[G]?{character}{text}	Defines glossary term
[G] {character}	Inserts text previously defined by
,	{character}
[G]*	Deletes all glossary definitions
[0]	in memory
[1]	Tabs to position set by [T]
[K]	Alpha lock; displays U on Data Line
[L]FILENAME,d#	Loads FILENAME into memory from
(-1	diskette in drive #
[L]#/markerl/marker2/	Copies specified text segment from
	memory to cursor position
[L]FILENAME,d#\	Displays FILENAME on screen
[L]?,d#	Lists file names on diskette in
[2].,="	drive #
[N]	Erases memory
[0]	DOS Commands Menu
[P]?	[P]rint/Program Commands Menu
[0]	Additional Functions Menu
[R]	Replace edit mode
[S]FILENAME,d#	Saves memory contents under FILENAME
[0]112221122	on diskette in drive #
[T]	Tab set/clear/purge
[v]	Accepts CTRL characters as text
F-1	entries; V appears on Data Line
[W]	Word delete or insert
[x]	Paragraph delete or insert
[Y]	Split screen enable/disable
[2]	Enable/disable word wrap-around;
<u> </u>	Z on Data Line when enabled

Apple Writer][Reference Card

PRINTING

Command	Effect	
[P]NP	Prints text currently in memory	
[P] CP	Continues printing	
[P]?	Displays print format options Default	Value:
LM{number}	Sets left margin to {number}	9
PM{number}	Indents/Outdents paragraph	0
	margin to {number}; value	
	relative to "LM"	
RM{number}	Sets right margin to {number}	79
TM{number}	Sets top margin to {number}	1
BM{number}	Sets bottom margin to {number}	1
PN{number}	Sets {number} of first page printed	1
PL{number}	Sets {number} of printed lines per	58
	page	
PI{number}	Sets page interval (form length)	
	to {number}	66
LI{number}	Sets {number} of spaces between lines	0
$SP{0 or 1}$	Selects continuous sheet feed {0} or	0
	single page {1} printing	
PD{number}	Selects print device destination slot	1
CR{0 or 1}	<pre>Selects {1}/deselects {0} line feed signal to printer</pre>	0
LJ	Left justify	
FJ	Fill justify	LJ
CJ	Center justify	
RJ	Right justify	
\mathtt{TL}	Specify top line headings	blank
BL	Specify bottom line headings	blank

The Print/Program commands and the commands which follow can be embedded in your text by preceding them with a carriage return and a period. Each text-embedded command must be entered on a separate line.

<pre>.FF .FF{number}</pre>	Form feed Conditional form food if loss than (number)
• rr (number)	Conditional form feed if less than {number} lines left on page being printed
•IN{text}	Stops printing and displays {text} on monitor
•EP{0 or 1)	Suppresses {0} or enables {1} printing