



Index

Cast of Characters

- * (asterisk) as prompt character 62
- ^ (caret) 122, 125
- :
- (colon) as Monitor command 105
- > (greater than sign) as prompt character 62
- ⌘ (Open Apple) 11-14, 228
- .
- (period) as Monitor command 102
- ø0 (phi 0) 162-163, 167, 170-172, 180-181
- ø1 (phi 1) 162-163, 167, 170-172, 180-181
- ø2 (phi 2) 162
- ?
- (question mark) as prompt character 62
-]
- (right bracket) as prompt character 62
- ⬢ (Solid Apple) 11-14, 228

A

- A1 92
- A2 92
- A4 92
- accumulator 138, 148
- ACIA 286
- address bus 161-162
- addressing
 - display pages 31-37, 174-179
 - indirect 77
 - I/O locations 138-139
 - RAM 139, 169-171
 - relative 121, 126, 137
 - ROM 168-169
- address transformation 177
- ALTCHAR soft switch 29
- alternate character set 19-20, 228
 - on original IIe 20

- ALTZP soft switch 84, 89-90
- analog inputs 42-43
- animation 231
- annunciators 40-41, 43
- any-key-down flag 13
- Apple keys 11-14
 - differences in Apple II family 228
- Applesoft BASIC xxi, 12, 105, 235
 - and lowercase xxii
 - and uppercase 48-49
 - 80-column support xxi
 - tabbing with original Apple IIe 271-272
 - use of page 3 78
 - use of page zero 77, 79-81
- Apple II compatibility with Apple IIe 48-50
- Apple II family differences 227-232
- Apple IIc interrupt differences 156
- Apple IIe, differences between
 - original and enhanced xix-xxiii
- ASCII input mode 107
- COUT1 subroutine 56
- interrupt support 132, 148-149
- microprocessor 6
- Mini-Assembler 123-125
- Monitor Search command 110
- MouseText 12, 20
- slot 3 144
- tabbing in Applesoft 271-272
- using Caps Lock 49
- Apple IIe 80-Column Text Card 86, 134, 267-275
- Apple IIe Extended 80-Column Text Card 86, 134, 267-275
- A register 146
- arithmetic, hexadecimal 116
- arrow keys 61, 63-64
- ASCII codes 14-16
- ASCII input mode 106-107

- assemblers 121
 - assembly language 234
 - asterisk (*) as prompt character 62
 - auxiliary firmware 86-93
 - auxiliary memory 86-93
 - differences in Apple II family 229
 - map 87
 - moving data to 92
 - soft switches 89
 - subroutines 91
 - auxiliary RAM 86-88
 - auxiliary slot 7, 49
 - differences in Apple II family 229
 - signals 197-200
 - AUXMOVE subroutine 91-92
- ## B
- backspacing 63
 - bank-switched memory 82-86, 87, 229
 - map 82
 - bank switches 83-85
 - reading 86
 - BASIC, Applesoft *See* Applesoft BASIC
 - BASIC, Integer *See* Integer BASIC
 - BASICIN subroutine 58, 220
 - address in I/O link 53
 - BASIC Monitor command 115
 - BASICOUT subroutine 65, 220
 - address in I/O link 53
 - baud rate for SSC 279
 - BEL character 53
 - BELL subroutine 221
 - BELL1 subroutine 39, 221