

I, J

- identification byte xx, 231
- IN# command 115
- index register 138
- indirect addressing 77
- input buffer 78
- INPUT command 269
- input devices *See* I/O devices
- input/output *See* I/O
- Input/Output Unit (IOU) 5, 6, 166–167, 186–187
- inputs
 - analog 38, 42–43
 - hand control 38
 - secondary 38–43
 - switch 41–42, 43
 - See also* I/O devices
- Integer BASIC 12, 235
 - and bank-switched memory 82
 - and reset 83
 - and uppercase 49
 - use of page 3 78
 - use of page zero 77, 79–81
- interpreter ROM 5
- interrupt handler
 - built-in 147, 151
 - user's 154–155
- interrupts 147–156
 - and card in auxiliary slot 50
 - daisy chain 193, 204
 - definition 147
 - original Apple IIe differences 148
 - priority 147
 - sequence 152
- interrupt vector 151
- INT IN pin 147
- INT OUT pin 147
- INVERSE command 270–271
- inverse display format 19–20, 57–58, 114

I/O

- addressing 138–139
- circuits 186–191
- devices, built-in 9–43
- entry points 145–146
- firmware, built-in 45–71
- links 51, 78, 140–141
- memory for peripheral cards 133
- memory map 142
- Pascal protocol 68–76, 144, 145–146
- switching memory 142–143
- IOREST subroutine 223
- IOSAVE subroutine 223
- I/O SELECT' signal 133–134
- IOU (Input/Output Unit) 5, 6, 166–167, 186–187
- IOUDIS soft switch 30
- IRQ vector 147–148
- IRQ' signal 148

K

- KBD' signal 187
- keyboard 3, 10–16
 - automatic repeat function 10
 - circuits 187–188
 - differences in Apple II family 227
 - memory locations 12
 - rollover 10
- KEYBOARD command 115
- keyboard encoder 5, 12
- keyboard ROM 5
- keyboard strobe 13
- KEYIN subroutine 58, 59–60, 223
 - address in I/O link 51
- keypad 188
- keys and ASCII codes 14–16
- KSW link 140

L

- language card 86
 - differences in Apple II family 229
- LED 2
- Left Arrow 63
- LF character 53, 54
- line feeds with SSC 281
- links, I/O 51
 - address storage 78
 - changing 140–141
- LIST command 121–122
- low-resolution graphics 17, 18, 21–23
 - colors 23
 - display pages 27
 - generation 181–182
 - map 35
 - with TV set 16

M

- machine language 120–122
- mapping display addresses 175–177
- maps *See* memory maps
- memory
 - addressing 168
 - auxiliary 86–93
 - bank-switched 82–86, 87, 229
 - changing contents 105–110
 - display 174–178
 - dump 102–104
 - examining 102
 - filling 117–118
 - for peripheral cards 132–136
 - I/O space 142–143
 - organization 74–98
 - sharing 91
 - text window locations 56–57
 - used by SSC 287
- Memory Management Unit (MMU) 5, 6, 164–165