

T

- tabbing 271–272
- TAB command xxi
 - with original Apple IIe 271–272
- television set 16
- temperature
 - case 159
 - operating 158
- text cards 86, 134, 150, 267–275
- text character sets
 - alternate 19–20
 - primary 19–20, 228
- text display 19–21, 22, 178–181
 - flashing format 57–58
 - inverse format 19, 57–58
 - normal format 19
 - See also* 40-column text;
80-column text
- text Page 1 27, 78
- text Page 2 27, 79
- TEXT soft switch 29
- text window 56–57
 - memory locations 57
- timing signals
 - expansion slots 194
 - RAM 172
 - 65C02 microprocessor 162–163
 - video 180–181, 184

U

- US character 55
- user's interrupt handler 154–155

V

- vectors
 - BRK 148
 - interrupt 151
 - IRQ 147–148
 - page 3 97
 - reset 96–97
- VERIFY command 109, 118
- VERIFY subroutine 226
- vertical sync 231
- VID7M signal 163
- video counters 173–174
- video display *See* display, video
- video monitor 16–17
 - connector 8, 186
- video output signals 185–186
- video ROM 5
- video standards 173
- VLIN subroutine 68, 226
- voltage
 - line 158
 - supply 159
- VTABZ subroutine 68
- VT character 54

W

- WAIT subroutine 226
- warm-start reset 95
- WRITE subroutine 39, 226
- WRITE tape command 111–112

X

- XFER subroutine 91, 93, 144, 153
- X register 146

Y

- Y register 146

Z

- zero page 77, 79–81