

**Table H-11 (continued)**  
Scratchpad RAM locations used by the SSC

Address	Field name	Bit	Interpretation
\$05F8+s	CMDBYTE	0-6	Printer mode default is Control-I; communications mode default is Control-A.
		7	Set to 1 to Zap control commands.
\$0678+s	STSBYTE		Status and IORESULT byte.
\$06F8+s	CHNBYTE	0-2	Current screen slot (communication mode); when slot = 0, chaining is enabled.
		3-7	\$Cs00 space entry point (communications mode).
	PWDBYTE	0-7	Current printer width; for listing compensation, auto-CR (printer mode).
\$0778+s	BUFBYTE	0-6	One-byte input buffer (communications mode); used in conjunction with XOFF recognition.
		7	Set to 1 when buffer full (communications mode).
	COLBYTE	0-7	Current-column counter for tabbing and so forth (printer mode).
\$07F8+s	MISCFLG	0	Generate line feed after CR when 1.
		1	Printer mode when 0; communications mode when 1.
		2	Keyboard input enabled when 1.
		3	Control-S (XOFF), Control-R, and Control-T input checking when 1.
		4	Pascal operating system when 1; BASIC when 0
		5	Discard line feed input when 1.
		6	Enable lowercase and special-character generation when 1 (communications mode).
		6	Tabbing option on when 1 (printer mode).
		7	Echo output to Apple IIe screen when 1.