

Appendix H discusses programming on the Apple IIe with the Apple Super Serial Card.

Appendix I describes the international keyboards and character sets. This appendix also contains schematic diagrams of the international circuit boards.

Appendix J contains the source listing of the Monitor firmware. You can refer to it to find out more about the operation of the Monitor subroutines listed in Appendix B.

Following Appendix J is a glossary defining many of the technical terms used in this manual. Some terms that describe the use of the Apple IIe are defined in the glossaries of the other manuals listed earlier.

Following the glossary is a selected bibliography of sources of additional information.

---

---

## The Apple IIe family

Changes have been made in the Apple IIe since the original version was introduced. The first change resulted in a version called the *enhanced Apple IIe*. The latest version is called the *extended keyboard Apple IIe*. These versions are all described in this manual. Where there are differences between the original Apple IIe, the enhanced IIe, and the extended keyboard IIe, they will be called out in the manual. Otherwise, the three machines operate identically.

---

## Identifying your Apple IIe

You can tell whether you have an enhanced or an original Apple IIe when you start up your computer: an original IIe will display "Apple ][ " at the top of the monitor screen, while the enhanced Apple IIe will display "Apple //e". The extended keyboard Apple IIe is easily identified by the numeric keypad built into the keyboard.